

EPS Eco

EPS ECO SE/SA 8KVA 1P 1ELM

Central Power Supply compliant with EN 50171 standards
Long battery autonomy and fast recharge times (< 12 hours)
Continuous overload of 120%
10-year life batteries

Order code 17715K

Technical specifications

INPUT

Voltage	220 / 230 / 240 V single-phase + N
Voltage tolerance	230 V $\pm 20\%$ at full load
Frequency tolerance	46 - 54 Hz
Power factor	≥ 0.99

OUTPUT and INVERTER OUTPUT

Rated power	8000 VA
Active power	8000 W
Power according with EN 50171	6400 VA / 6400 W
Output Voltage	220 / 230 / 240 V single-phase + N
Crest factor (I _{peak} /I _{rms})	3 : 1
Waveform	Sinusoidal
Frequency	50 / 60 Hz (selectable)
Voltage distortion with non-linear load	$\leq 4\%$
Voltage distortion with linear load	$\leq 1\%$

BATTERIES - AUTONOMY

AGM-VRLA	20x 55Ah - 10 YEARS expected lifespan
Autonomy	1h
Maximum recharge current	4 A

ENVIRONMENTAL

Color	Black
Communication	LCD display / slot for communication interface / RS-232/USB
Accessories provided	USB cable, Monitoring Software
Protections	Overvoltage - undervoltage - temperature - excessive low battery
Noise (at 1 m)	<58 dBA
Operating temperature	0 °C - +40 °C Batteries 20 °C - +25 °C
Relative humidity	20-95% non-condensing
Type of sockets	Terminal block
Protection rating	IP20
Weight EPS Eco	27 kg
Dimensions (h w d) EPS Eco	580x250x595 mm
Weight Battery cabinet	37 kg
Dimensions (h w d) Battery cabinet	1190x950x470 mm
Weight Battery	346 kg



Certificates and standards

EN50171 - European directives: L V 2014/35/EU low voltage; EMC 2014/30/EU electromagnetic compatibility -- Directive and Standards: Safety IEC EN 62040-1; EMC IEC EN 62040-2; RoHS compliant -- Classification in accordance with IEC 62040-3 VFI - SS - 111

Accessories



16323
MODULO RS485 LG EPS ECO