



StripLED High Performance

STRIP LED HP 18W IP65 3K



StripLED 24V



Codice ordine 56674

EAN 8002219880048

Specifiche tecniche

Potenza assorbita	18 W
Tipo di tensione di alimentazione	DC
CCT tonalità luce	3000 K
Numero LED	120
Numero LED/metro	120,00
Rischio fotobiologico	RG0
Watt/metro	18 W/m
Angolo fascio luminoso	120 °
Stabilità colore	SDCM6
Consumo (1000h)	18 KWh
CRI Resa cromatica	>80
Dimmerabile	Si
Efficienza	111 lm/W
Classe di efficienza energetica sorgente luminosa	F
Codice Eprel	777178
Fattore di potenza	1
Vita	50000 h
Flusso sorgente luminosa	2000 lm
Flusso per metro	2000 lm/m
Flusso luminoso L70B50	50000 h
Tensione alimentazione (DC)	24 Vdc



Specifiche meccaniche

Altezza	4 mm
Lunghezza	5000 mm
Larghezza	10 mm
Lunghezza di taglio Strip	50 mm
Grado di protezione IP	IP65

Certificati e normative

UK SI 2021 No. 1095, EN 62471:2008, EN 60598-2-20:2015 + AC:2017-01, EN IEC 60598-1:2021, EN IEC 63000:2018, EN 62493:2010, EN 61000-3-3:2013, REG. 2019/2020(EU), EN IEC 55015:2019 + A11:2020, EN IEC 61000-3-2 :2019

Accessori





56691
KIT PROF CARTONGESS CON
MOLLE



56690
KIT PROF PLAFO LARGO



4717
DRIVER ISOLATO 24V IP67
75W





4727
DRIVER PUSH TO DIM
24VIP67 100



56628
KIT PROFILO 2MT STRIP
DISSIPAT



56623
CONN STRIP TO DRIVER IP65
3Pz



4716
DRIVER ISOLATO 24V IP67
60W



56627
KIT PROFILO 2MT STRIP ANG



4730
DRIVER PUSH TO DIM
24VIP67 300



56695
KIT PROF 2MT STRIP INCASS



4718
DRIVER ISOLATO 24V IP67
100W



56694
KIT PROF 2MT STRIP PLAFO



4728
DRIVER PUSH TO DIM
24VIP67 150



56692
KIT PROF CARTONGESS
RASATURA



56693
KIT PROF CARTONGES RASAT
LARGO



4729
DRIVER PUSH TO DIM
24VIP67 200



56624
C STRIP TO STRIP FILO IP65
2PZ



56696
KIT PROF INC FONDO
CARTONGESS



4719
DRIVER ISOLATO 24V IP67
150W